



Offer 351238

BOBST AMBITION 76 A1 from 2020

Folder Gluer



Offer Details

Offer Number:	351238
Brand:	BOBST
Model:	Ambition 76 A1
Manufacturer	BOBST
Condition:	Very good
Year:	2020
Incoterm:	Free Carrier
Cylinders Condition:	
Under Power:	No
Still in production:	No
Test possible:	No
Complete and in working condition:	Yes
Availability:	Immediately
Counter:	
Machine number:	
Description:	<p>CUBE adjusting system<>Carton board: max 800 g/m2<>Corrugated flute type: N, E, F<>Speed: 20 to 300 m/min<>Inching speed: 20 m/min<>Box sizes:<>Straight line "C": 126 to 760 mm<>Straight line "E": 60 to 800 mm<>Straight line "L": 60 to 385<>Crash-lock bottom "C" (2): 146 to 760 mm<>Crash-lock bottom "L": 70 to 385 mm<>FEEDER Total length: 610 mm<>6 Feed conveyors with 30 mm wide belt with 4 built-in mechanical vibrators<>1 Thickness gauge with lateral and lengthwise setting and upper introduction rollers <>1 Additional thickness gauge with lateral and lengthwise setting and upper introduction rollers<>2 Side guides in two parts <>Asymmetrical and adjustable in length <>Max. pile height: 350 mm. <>1 set o rear guides for blank support <>1 Motor controlled by frequency variator to drive the feed belts and to put in o out of operation <>PREBREAKER SECTION total length: 2300 mm. <>1 lower left conveyor with 43 mm wide belt<>1 Lower right conveyor with 25 mm wide belt<>1 Set of upper conveyors with 25 mm wide belts and lifting device<>1 Left</p>

hand prebreaker without belt with built-in pressing device<>Adjustable through eccentric<>Max. width of the glue flap: 30 mm<>1 Reopening guide<>1 Right-hand prebreaker with 30 mm belt width<> Including a system to set the prebreaking angle<>1 Lower central supporting guide<>GLUING UNIT<>1 Lower left-hand gluing unit with wheel and double scraper<>1 HHS gluing system with 2 nozzles, upgradeable up to 4<>1 Removable glue basin<>1 Upper guide with pressure roller<>1 Refill bottle<>Additional options installed (with factory no.):<>A-012 Delivery, extended version<>B-012 Device for CRASH LOCK BOTTOM boxes without prebreaking of 3rd crease<>B-060 Device for sleeves and envelopes<>EA-015 Electric pile vibrator<>For the rear pile guides. Improves the feeding o blanks which are sticking to each other<>EA-025 Blank suction device<>EA-030 Rotary brushes<>F-020 Long upper right conveyor outlet<>G-001 Minimum folding device<>G-015 Central conveyors<>J-001 Infeed device left and right Infeed device with 30 mm belt width<>J-010 Upper pressure belt<>J-014 Additional upper pressing belt<>DX-027 Glue application system without possibility of quality assuranc (maximum machine speed 300 m/min)<>K-012 Flipper ejector<>KX-012 Code reader "Stand-Alone"<>Xtend series Baumerhhs (maximum machine speed 700 m/min)<>Dismantled<>I stock

Technical details

Max. blank width	760 mm
Min. blank width	126 mm
HS Code	84439959 HS Codes Classification of Other

PRICE: Upon request

Images



Contact: +49 172-371-8407 Email: